

ADVR7008DA-LM-V2
2 SATA 8ch Analog HD DVR



Features:

- Support AHD-H series front-end non real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7008DA-LM-V2

Interface:

Parameter:

| | Model | ADVR7008DA-LM-V2 |
|------------------------|-------------------|--|
| System | Main processor | Hi3520D V300 |
| Video | video codec | H.264 |
| | Encode | 8*1080N@12fps |
| | Decode | 4*1080N@12fps |
| Audio | Multi-mode input | Pure Analog: 8*1080N; 4*AHD-H; 4*1080N; Mixed : 2*AHD-H (Analog) +2*1080P (Network) ; Pure Network: 8*1080P; 8*960P; 4*3M; ; |
| | Audio compression | G.711A |
| Recording and Playback | Intercom | support |
| | Record mode | Manual>alarm>motion detection>timing |
| Storage and backup | Playback Channels | 4 (pure local input mode) |
| | Backup mode | Network backup、USB HDD、USB writer、SATA writer |
| Interface | Video input | 8 BNC |
| | Video output | 1ch VGA,1ch HDMI |
| | Audio input | 8ch RCA |
| | Audio output | 1ch RCA |
| | Alarm input | 4 |
| | Alarm output | 1 |
| | Network interface | RJ45 10M/100M Adaptive Ethernet port |
| | PTZ control | RS485; support multiple PTZ protocols |
| | USB | 2 USB ports |
| | Hard disk | 2 SATA (Each maximum support 6T) |
| Other | Wireless | 3G、WIFI(expand via USB) |
| | Power | 12V/4A |
| | dimension | 350mm(length)* 296mm(width)* 44mm(height) |