

**ADVR7008DA-M**  
2 SATA 8ch Analog HD DVR



**Features:**

- Support AHD-M series front-end real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

**Model:**

**ADVR7008DA-M**

**Interface:**

**Parameter:**

|                        | Model                   | ADVR7008DA-M  |
|------------------------|-------------------------|---|
| System                 | Main processor          | Huawei Hi 3531  |
| Video                  | video compression       | H.264(High Profile);  |
|                        | Encode                  | 8*AHD-M   |
|                        | Decode                  | 8*AHD-M   |
|                        | Multi-mode input        | Pure Analog: 8*AHD-M; 8*AHD-L;<br>Mixed: 4*AHD-M( Analog )+4*720P( Network );<br>8*AHD-M (Analog) +8*720P (Network)<br>Pure Network : 1*1080P+8*720P; 4*1080P;<br>20*960H |
| Audio                  | Audio compression       | G.711A  |
|                        | Intercom                | support   |
| Recording and Playback | Record mode             | Manual>alarm>motion detection>timing  |
|                        | Playback Channels       | 8 (pure local input mode)   |
| Storage and backup     | Space occupation        | 960H: 12~20G/ day*channel<br>720P: 20G~30G/ day*channel<br>audio: 691.2M/ day*channel   |
|                        | Backup mode             | Network backup、USB HDD, USB writer、SATA writer  |
| Interface              | Video input             | 8 BNC   |
|                        | Video output            | 1ch VGA,1ch HDMI  |
|                        | Audio input             | 6ch RCA   |
|                        | Audio output            | 1ch RCA   |
|                        | Alarm input             | 4   |
|                        | Alarm output            | 1   |
|                        | Network interface       | RJ45 10M/100M Adaptive Ethernet port  |
|                        | PTZ control             | RS485; support multiple PTZ protocols   |
|                        | USB                     | 2 USB ports   |
|                        | Hard disk               | 2 SATA ( Each maximum support 4T )  |
| Wireless               | 3G、WIFI(expand via USB) |   |
| Other                  | Power                   | 12V/4A  |
|                        | dimension               | 350mm(length)* 296mm(width)* 44mm(height)   |