

**ADVR7016B-LM**  
**2 SATA 16ch Analog HD DVR**



**Features:**

- Support AHD-M series real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

**Model:**

**ADVR7016B-LM**

**Interface:**

**Parameter:**

	Model	ADVR7016B-LM
System	Main processor	Hi 3531
Video	video codec	H.264
	Encode	16*AHD-M
	Decode	1*AHD-M
Video	Multi-mode input	Pure Analog: 16*AHD-M; 8*AHD-M; 16*AHD-L; Mixed: 4*AHD-M (Analog) +4*720P (Network) ; 8*AHD-M (Analog) +8*720P (Network) ; Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H;
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	16 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	6ch RCA
	Audio output	1ch RCA
	Alarm input	4
	Alarm output	1
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2 SATA (Each maximum support 6T )
Wireless	3G、WIFI(expand via USB)	
Other	Power	12V/4A
	dimension	310mm(length)* 298mm(width)* 60mm(height)