

ADVR7016C-LM/A-V2
1 SATA 16ch Analog HD DVR



Features:

- Support ADH-M series front-end real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7016C-LM/A-V2

Interface:

Parameter:

	Model	ADVR7016C-LM/A-V2
System	Main processor	Hi3521A
Video	video compression	H.264
	Encode	16*1080N@12fps
	Decode	16*1080N@12fps
Audio	Multi-mode input	Pure Analog: 16*1080N; 8*1080N; ; Mixed: 8*1080N (Analog) +8*960P (Network) Pure Network: 8*1080P; 16*960P; 4*3M; 4*5M
	Audio compression	G.711A
Recording and Playback	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Storage and backup	Playback Channels	4 (pure local input mode)
	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	16 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	6ch RCA
	Audio output	1ch RCA
	Alarm input	4ch
	Alarm output	1ch
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	1 SATA (Each maximum support 4T)
Other	Wireless	3G、WIFI(expand via USB)
	Power	12V/2A
	dimension	310mm(length)* 230mm(width)* 44mm(height)