

ADVR7016E-M
2 SATA 16ch Analog HD DVR



Features:

- Support AHD-M series front-end real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7016E-M

Interface:

Parameter:

	Model	ADVR7016E-M
System	Main processor	Huawei Hi 3531+3532
Video	video compression	H.264(High Profile):
	Encode	16*AHD-M
	Decode	16*AHD-M
Audio	Multi-mode input	Pure Analog: 16*AHD-M; 16*AHD-L; Mixed:4*AHD-M (Analog) +4*720P (Network) 8*AHD-M (Analog) +8*720P (Network) Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H;
	Audio compression	G.711A
Recording and Playback	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Storage and backup	Playback Channels	16 (pure local input mode)
	Space occupation	960H: 12~20G/ day*channel 720P: ~20G/ day*channel audio: 691.2M/ day*channel
Interface	Backup mode	Network backup、USB HDD、USB writer、SATA writer
	Video input	16 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	8ch RCA
	Audio output	1ch RCA
	Alarm input	8
	Alarm output	1
	Network interface	RJ45 10M/100M/1000M Adaptive Ethernet port
	PTZ control	One RS485, one RS232; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2 SATA (Each maximum support 4T)
Wireless	3G、WIFI(expand via USB)	
Other	Power	12V/4A
	dimension	440mm(length)* 290mm(width)* 50mm(height)