

ADVR7032E-LM
2 SATA 32ch Analog HD DVR



Features:

- Support AHD-M series front-end non-real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7032E-LM

Interface:

Parameter:

	Model	ADVR7032E-LM							
System	Main processor	Hi 3531+ Hi 3532							
	Video	<table border="1"> <tr> <td>video codec</td> <td>H.264</td> </tr> <tr> <td>Encode</td> <td>32*AHD-M@12fps</td> </tr> <tr> <td>Decode</td> <td>8*AHD-M@12fps</td> </tr> <tr> <td>Multi-mode input</td> <td>Pure Analog: 32*AHD-M,24*AHD-M, 16*AHD-M,16*AHD-L Mixed:4*AHD-M (Analog) +4*720P (Network) Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H;</td> </tr> </table>	video codec	H.264	Encode	32*AHD-M@12fps	Decode	8*AHD-M@12fps	Multi-mode input
video codec	H.264								
Encode	32*AHD-M@12fps								
Decode	8*AHD-M@12fps								
Multi-mode input	Pure Analog: 32*AHD-M,24*AHD-M, 16*AHD-M,16*AHD-L Mixed:4*AHD-M (Analog) +4*720P (Network) Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H;								
Audio	Audio compression	G.711A							
	Intercom	support							
Recording and Playback	Record mode	Manual>alarm>motion detection>timing							
	Playback Channels	8 (pure local input mode)							
Storage and backup	Space occupation	960H: 12~20G/ day*channel 720P: ~20G/ day*channel audio: 691.2M/ day*channel							
	Backup mode	Network backup、USB HDD、USB writer、SATA writer							
Interface	Video input	32 BNC							
	Video output	1ch VGA,1ch HDMI							
	Audio input	16ch RCA							
	Audio output	1ch RCA							
	Alarm input	8							
	Alarm output	1							
	Network interface	RJ45 10M/100M/1000M Adaptive Ethernet port							
	PTZ control	One RS485, one RS232; support multiple PTZ protocols							
	USB	2 USB ports							
	Hard disk	2 SATA (Each maximum support 6T)							
	Wireless	3G、WIFI(expand via USB)							
Other	Power	12V/4A							
	dimension	440mm(length)* 290mm(width)* 50mm(height)							