

ADVR7032F-LM-V2
4 SATA 32ch Analog HD DVR



Features:

- Support 1080N non-real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7032F-LM-V2

Interface:

Parameter:

	Model	ADVR7032F-LM-V2
System	Main processor	Hi 3531A
Video	video codec	H.264
	Encode	32*1080N@15fps
	Decode	8*1080N@15fps
Audio	Multi-mode input	Pure Analog: 32*1080N,24*1080N, 16*1080N, Mixed: 4*1080N (Analog) +4*1080N (Network) Pure Network: 32*1080P, 16*3M, 8*5M;
	Audio compression	G.711A
Recording and Playback	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Storage and backup	Playback Channels	8 (pure local input mode)
	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	32 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	16ch RCA
	Audio output	1ch RCA
	Alarm input	16
	Alarm output	4
	Network interface	RJ45 10M/100M/1000M Adaptive Ethernet port
	PTZ control	One RS485, one RS232; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	4 SATA (Each maximum support 6T)
Other	Wireless	3G、WIFI(expand via USB)
	Power	12V/6A
	dimension	440mm(length)*400.5mm(width)*60mm(height)