

**ADVR7108K-H**  
**8 SATA 8ch Analog HD DVR**



**Features:**

- Support ADH-H series front-end real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

**Model:**

**ADVR7108K-H**

**Interface:**

**Parameter:**

	Model	ADVR7108K-H
System	Main processor	Hi3531+Hi3532
Video	video codec	H.264
	Encode	8*AHD-H
	Decode	4*AHD-H
Audio	Multi-mode input	Pure Analog: 8*AHD-H; 8*AHD-M; Mixed: 2*AHD-H(Analog)+2*1080P(Network); Pure Network: 1*1080P+8*720P; 4*1080P; 20* 960H
	Audio compression	G.711A
Recording and Playback	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Storage and backup	Playback Channels	4 (pure local input mode)
	Space occupation	960H: 12~20G/ day*channel 720P: ~20G/ day*channel 1080P 20~30 G/ day*channel audio: 691.2M/ day*channel
Interface	Backup mode	Network backup、USB HDD, USB writer、SATA writer
	Video input	8 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	8ch RCA
	Audio output	1ch RCA
	Alarm input	16
	Alarm output	4
	Network interface	RJ45 10M/100M/1000M Adaptive Ethernet port
	PTZ control	One RS485, one RS232; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	8 SATA ( Each maximum support 6T )
	Wireless	3G、WIFI(expand via USB)
Other	Power	DVR dedicated ATX Power Supply
	dimension	443mm(length)* 427.5mm(width)* 92mm(height)