

**ADVR7808R-EL(HDMI)
1 SATA 8ch Analog HD DVR**



Features:

- Support D1 series front-end real-time encoding,AHD-L series front-end non-real-time encoding;
- Support VGA, TV,HDMI output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

ADVR7808R-EL(HDMI)

Interface:

Parameter:

	Model	ADVR7808R-EL(HDMI)
System	Main processor	Huawei Hi 3520D
Video	video codec	H.264(High Profile);
	Encode	8*D1 /8*AHD-L@12fps
	Decode	1*D1 /2*AHD-L@12fps
Audio	Multi-mode input	Pure Analog: 8*AHD-L: 8*D1; 8*HD1; Mixed: 2*D1(analog) +1*720P (network) +1* 1080P(network); Pure Network: 4*1080P; 4*720P; 8*720P; 8*1080P; 1*1080P
	Audio compression	G.711A
Recording and Playback	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Storage and backup	Playback Channels	2 (pure local input mode)
	Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
Interface	Backup mode	Network backup、USB HDD, USB writer、SATA writer
	Video input	8 BNC
	Video output	1ch VGA, 1ch TV,1ch HDMI
	Audio input	1ch RCA
	Audio output	1ch RCA
	Alarm input	NO
	Alarm output	NO
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	NO
	USB	2 USB ports
	Hard disk	1 SATA (Each maximum support 6T)
Wireless	No	
Other	Power	12V/2A
	dimension	210mm(length)* 200mm(width)* 49mm(height)