

AHB 7008R-LM



(To prevail in kind)

Feature:

- ➤ HD iDVR Three in one: DVR / HVR / NVR features 3-in-1, multi-mode input, support eight analog video encoding, support for high-definition video mixing analog inputs + network support pure HD network video input.
- > Step on the Internet: With XM cloud service, easy to achieve a variety of network penetrations ,one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate.
- ➤ Compression algorithm ideal: H.264 High Profile compression algorithm,30% decrease of stream due to advanced space-time filtering technology.
- ➤ Playback quality: Supports full real-time encoding video, full real-time playback of multi-channel synchronous decoding.
- ➤ Main and Sub Stream: Main stream and Sub-stream encoding. Main stream for local storage, ensure image quality; Sub-stream for real-time network transmission, easy to solve bandwidth bottleneck problem.
- ➤ **Mobile monitor:** Support various mobile monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android).
- ➤ **Display:** VGA HD output simultaneously,support VGA 1080p HD output,lead the technology of HD resolution.
- ➤ **Operation interface:** Similar to Windows operating style, easy to get started with powerful mouse right-click function.
- ➤ **Network:** Powerful network services (support DHCP, PPPOE, FTP, DNS, DDNS, EMAIL,IP searches etc.) And perfect support (WEB, Client, SDK), easy to achieve interoperability.
- **Browsers:** Support IE, Chrome, Firefox, Safari browsers.
- Remote Access: With DNS (ARSP),easy to monitor remotely,3322 (Greek network), dyndns, oray (peanut shells), myq-see and other DNS are also provided.
- ➤ **Differentiation:** Boot screen free replacement, more than twenty languages, over 10 sets of GUI interface, ten kinds of remote control, which make our products different from others.
- ➤ Others: With unique black box technology, the whole process can be monitored, which greatly reduces maintenance costs.



Specification:

	Model	AHB7008R-LM
System	Main processor	Hi3521
	Operating system	embedded Linux
	System resources	Simultaneously multi-channel real-time recording, playback, network
		operation, USB backup
Interface	Operator interface	support 16-bit true color graphical menu interface and mouse operation
	Preview	1/4/8/9
Video	Codec	H.264
	Monitor quality	VGA: HD
	Playback quality	AHD-M/ AHD-L/D1
	Encode ability	8*AHD-M
	Decode ability	1*AHD-M
	Multi-mode input	analog: 8*AHD-M; 4*AHD-M; 8*AHD-L;
		hybrid: 4*AHD-M (analog) +4*720P (network)
		Network only: 2*1080P+2*720P; 8*720P;
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level
	Wotton Detection	sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
Auulu	Intercom	support
Record &	Record mode	manual>alarm>motion detection>timing
playback	Local Playback	4ch(local input mode)
	Search mode	Search by time, calendar, event, channel
	Space occupation	720P ~20G/ day*channel;960H 12~20G/ day*channel;audio: 691.2M/
Storage		day*channel
& backup	Video storage	HDD, network
	Backup mode	Network, USBhard disk, USB burner, SATA burner
	Video input	8ch BNC
	Video output	1ch VGA
	Loop Vout	N/A
	Audio input	1ch RCA
	Audio output	1ch RCA
External Interface	Alarm input	0
	Alarm output	0
	Network interface	RJ45 10M/100M
	PTZ control	0
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Max 4TB/per)
	Wireless	3G, WIFI (extend via USB)



	Power supply	12V/2A
	Power	<15W (without HDD)
	Consumption	<13W (Without HDD)
General	Temperature	0°C-+55°C
	Humidity	10% — 90%
	Working	86kpa—106kpa
	environment	оокра 100кра
	Dimension	136mm*81mm
	Weight	135g