



## AHB 7016T4-MH-V2



### Feature:

- Support VGA, HDMI full HD output simultaneously;
- support ONVIF; access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support various mobile phone、pad monitoring (ios, android);
- Remote Access, With DNS (ARSP),easy to monitor remotely

### Specification:

	<b>Model</b>	AHB7016T4-MH-V2
System	Main processor	Hi3531A
Interface	Preview	1/4/8/9/16
Video	Codec	H.264
	Monitor quality	VGA,HDMI: HD
	Preview ability	16*1080P
	Encode ability	16*1080N/16*1080P@12fps
	Decode ability	16*1080N/16*1080P @12fps
	Multi-mode input	analog: 16*1080P;8*1080P;16*1080N; hybrid: 8*1080P (analog) +8*1080P (network) Network only: 8*1080P+ 8*960P;8*3M ;4*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	16ch(local input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	16ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	0 (Can be extended to 16ch) /1
	Alarm I/O	0 (Can be extended to 16ch) /0 (Can be extended to 4ch)
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	0 (Can be extended to 1*RS485, 1*RS232; Support kinds of PTZ protocols)
	USB	2* USB 2.0 ports
	HDD	4*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
	General	Power supply
Power Consumption		<15W (without HDD)
Working environment		Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
Dimension		235mm*90mm
Weight		279g

