



AHB7032F8-LM-V2



Feature:

- Support VGA, HDMI full HD output simultaneously;
- support ONVIF; access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP),easy to monitor remotely

Specification:

	Model	AHB7032F8-LM-V2
System	Main processor	Hi3531A
Interface	Preview	1/4/8/9/16/24/32
Video	Codec	H.264
	Monitor quality	VGA,HDMI: HD
	Encode ability	32*1080N@15fps
	Decode ability	8*1080N@15fps
	Onvif	support
	Multi-mode input	analog: 32* 1080N, 24*1080N, 16* 1080N; hybrid: 8* 1080N (analog) +8* 960P (network) Network only: 32*1080P, 16*3M, 8*5M;
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	8ch(local input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	32ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	16 /1
	Alarm I/O	16 / 4
	Network interface	RJ45 10M/100M /1000M self-adaption
	PTZ control	1*RS485, 1*RS232, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	8*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	DVR dedicated ATX Power Supply
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	282mm*142mm
	Weight	259g

