

AHB7804R-MH-V3

1080N 5 in 1 AHD Main Board



Specification:

Features:

- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support AHD/TVI/CVI/CVBS/IP five signals;
- Support XVI, image quality is better;

Model:

AHB7804R-MH-V3

	Model	AHB7804R-MH-V3
System	Main	Hi3520D V300
	Codec	H.264
Video	Monitor	VGA;HDMI
	Preview ability	4*5M-N@20fps (5 in 1); 4*4M-N (5 in 1); 4*1080P(5 in 1)
	Encode ability	4*5M-N@12fps (5 in 1); 4*4M-N@15fps (5 in 1); 4*1080P@15fps(5 in 1)
	Decode ability	2*5M-N@12fps (5 in 1); 4*4M-N@15fps (5 in 1); 4*1080P@15fps (5 in 1)
	Multi-mode input	analog:4*1080P; hybrid:2*1080P (analog) +2*1080P (network) ;4*1080N (analog) +4*960P (network) ; network:16*1080P;9*1080P;16*960P;4*5M;
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
	Audio	Audio
Intercom		support
Record	Record mode	manual>alarm>motion detection>timing
	Search mode	Search by time, calendar, event, channel
	Video	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	4ch BNC
	Video	1ch VGA, 1ch HDMI
	Audio I/O	1/1
	Alarm I/O	0/0
	Network	RJ45 10M/100M self-adaption
	Extension interface	2* USB 2.0 ports
	HDD	2*SATA ports (Max 8TB/per)
General	Power	12V/4A
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	168mm*81mm
	Weight	125g