



AHB 7808R-EL



(To prevail in kind)

Feature:

- **HD iDVR Three in one:** DVR / HVR / NVR features 3-in-1, multi-mode input, support eight analog video encoding, support for high-definition video mixing analog inputs + network support pure HD network video input.
- **Step on the Internet:** With XM cloud service, easy to achieve a variety of network penetrations ,one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate.
- **Compression algorithm ideal:** H.264 High Profile compression algorithm,30% decrease of stream due to advanced space-time filtering technology.
- **Playback quality:** Supports full real-time encoding video, full real-time playback of multi-channel synchronous decoding.
- **Main and Sub Stream:** Main stream and Sub-stream encoding. Main stream for local storage, ensure image quality; Sub-stream for real-time network transmission, easy to solve bandwidth bottleneck problem.
- **Mobile monitor:** Support various mobile monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android) .
- **Display:** VGA HD output simultaneously,support VGA 1080p HD output,lead the technology of HD resolution.
- **Operation interface:** Similar to Windows operating style, easy to get started with powerful mouse right-click function.
- **Network:** Powerful network services (support DHCP, PPPOE, FTP, DNS, DDNS, EMAIL,IP searches etc.) And perfect support (WEB, Client, SDK), easy to achieve interoperability.
- **Browsers:** Support IE、 Chrome、 Firefox、 Safari browsers.
- **Remote Access:** With DNS (ARSP),easy to monitor remotely,3322 (Greek network), dyndns, oray (peanut shells), myq-see and other DNS are also provided.
- **Differentiation:** Boot screen free replacement, more than twenty languages, over 10 sets of GUI interface, ten kinds of remote control, which make our products different from others.
- **Others:** With unique black box technology, the whole process can be monitored, which greatly reduces maintenance costs.



Specification:

	Model	AHB7808R-EL
System	Main processor	Hi3520D
	Operating system	embedded Linux
	System resources	Simultaneously multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	support 16-bit true color graphical menu interface and mouse operation
	Preview	1/4/8/9
Video	Codec	H.264
	Monitor quality	VGA、HDMI: HD
	Playback quality	AHD-L /D1
	Encode ability	8*D1/8*AHD_L@12fps
	Decode ability	1*D1/2*AHD_L@12fps
	Multi-mode input	analog: 8*AHD-L/8*D1/8*HD1;; hybrid:2*D1 (analog) + 1*1080P(network)+1*720P(network) Network only: 8*1080P/4*720P/1*1080P/4*1080P/8*720P;
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)	
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	2ch(local input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Space occupation	720P ~20G/ day*channel ;960H 12~20G/ day*channel;audio: 691.2M/ day*channel
	Video storage	HDD, network
	Backup mode	Network, USBhard disk, USB burner, SATA burner
External Interface	Video input	8ch BNC
	Video output	1ch VGA, 1TV
	Loop Vout	N/A
	Audio input	1ch RCA
	Audio output	1ch RCA
	Alarm input	0
	Alarm output	0
	Network interface	RJ45 10M/100M
	PTZ control	0
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Max 4TB/per)
Wireless	0	



General	Power supply	12V/2A
	Power Consumption	<15W (without HDD)
	Temperature	0°C - +55°C
	Humidity	10% - 90%
	Working environment	86kpa - 106kpa
	Dimension	136mm*81mm
	Weight	135g