



AHB 7808R-MS-V3



Feature:

- Support VGA, HDMI full HD output simultaneously;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, etc.);
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, easy to control leading end through back end
- Support AHD/TVI/CVI/CVBS signal 4 in 1 input

Specification:

	Model	AHB7808R-MS-V3
System	Main processor processor	The newest processor
Interface	Preview	1/4/8/9
Video	Codec	H.264
	Monitor quality	VGA,HDMI: HD
	Encode ability	8*1080N@12fps
	Decode ability	4*1080N@12fps
	Multi-mode input	analog: 8*1080N support CVBS(960H/D1)
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch(local input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	8ch BNC
	Video output	1ch VGA, 1ch HDMI(not support audio)
	Loop Vout	N/A
	Audio I/O	1/1
	Alarm I/O	0/0
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	NO
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Max 8TB/per)
Wireless	N/A	
General	Power supply	12V/4A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	168mm*81mm
	Weight	182g