AHB8008R-LM

Feature:

- Support H.265 encoding, ultra-low bitrates, compatible with H.264 surroundings;
- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- > Remote Access, With DNS (ARSP),easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals;
- Support Digital to analog conversion Instant playback

Specification:

	Model	AHB8008R-LM
System	Main processor	Hi3520DV400
Interface	Preview	1/4/8/9
Video	Codec	H.265
	Monitor quality	VGA(1080P at most);HDMI(1080P at most)
	Preview ability	8*1080N (6 in 1)
	Encode ability	8*1080N@15fps (6 in 1)
	Decode ability	8*1080N@15fps (6 in 1)
	Multi-mode	Analog: 8*1080N;
	input	Digital to analog conversion: support
		network: 16*1080P; 8*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set
		(Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record &	Record mode	manual>alarm>motion detection>timing
playback	Local Playback	4ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage &	Video storage	HDD, network
backup	Backup mode	Network, USB hard disk, USB burner, SATA burner
External	Video input	8ch BNC
Interface	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	1/1
	Alarm I/O	0/0
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)





General	Power supply	12V/4A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0°C-+55°C, Humidity:10%-90%, Atm:86kpa-106kpa
	Dimension	168mm*80mm
	Weight	142g