

EJ IR Waterproof Box IP Camera Series



Model:

IPC-EJ5110PL-IR2、IPC-EJ5313PL-IR2 、IPC-EJ5320PL-IR2

Feature:

- High resolution, image presented vivid and clear.
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring.
- Support various information superimposed (such as: ID、IP、DDNS and so on), convenient to operate
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support dual-stream
- support various mobile long-distance monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support multiple web browsers (IE、Chrome、Firefox、Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF

specification

model	IPC-EJ5110PL-IR2	IPC-EJ5313PL-IR2	IPC-EJ5320PL-IR2
camera			
Image sensor	1/4" OV 9712 CMOS	1/3"AR0130 ultra-low illumination CMOS	1/2.8"SONYIMX122 ultra-low illumination CMOS
Min.illumination	Color:0.1Lux @(F1.2,AGC ON),0 LUX with IR Black/white:0.01 Lux @(F1.2,AGC ON),0 LUX with IR	Color:0.01Lux @(F1.2,AGC ON),0 LUX with IR Black/white:0.01Lux @(F1.2,AGC ON),0 LUX with IR	
Shutter	1/50(1/60)s-1/10,000s		
Lens	HD professional lens 3.6mm@ F1.8 (6mm,8mm,12mm)		

Lens mount	M12		
Day/night	Support IR-CUT		
compression			
video compression	H.264 HighProfile, JPEG snapshot		
bite rate	32 Kbps~6Mbps	32 Kbps~6Mbps	
audio compression	G.711a		
image			
Max.image reolution	1280*720	1280*960	1920*1080
Frame rate	50Hz:25fps (1280*720) 60Hz:30fps (1280*720)	50Hz:25fps(1280*720) (1280*960) 60Hz:30fps(1280*720) 25fps (1280*960)	50Hz:25fps(1920*1080)(704*576) 60Hz:30fps(1920*1080)(704*480)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client.		
network			
storage	Network storage		
intelligent alarm	Motion detection, video loss, cable break, IP address conflicts		
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,IPv6)		
basic	anti-flicker, dual-stream, heartbeat, password protection		
interface			
net interface	One RJ45 10M/100M		
Audio interface	1ch 3.5mm audio input		
general			
Working condition	-10℃~60℃ , humidity less than 90%(non-condensing)		
Power supply	DC12V±10%		
Power consumption	IR3:6W MAX;		
Protection range	IP66		
IR distance	IR2:20-30 meters;		
dimension	200mm*84mm*72mm		
weight	300g		