

EQ IR Waterproof Box IP Camera Series



Model:

IPC-EQ5110PE-IR1, IPC-EQ5110PL-IR1, IPC-EQ5313PL-IR1, IPC-EQ5320PL-IR1

Feature:

- High resolution, image presented vivid and clear.
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring.
- Support various information superimposed (such as: ID、IP、DDNS and so on), convenient to operate
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support dual-stream
- support various mobile long-distance monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support multiple web browsers (IE、Chrome、Firefox、Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF.

Specification:

| Model | IPC-EQ5110PE-IR1 | IPC-EQ5110PL-IR1 | IPC-EQ5313PL-IR1 | IPC-EQ5320PL-IR1 |
|--------------------|--|---|---|--|
| Camera | | | | |
| Image sensor | 1/4" OV 9712 CMOS | | 1/3"AR0130ultra-low illumination CMOS | 1/2.8"SONYIMX122 ultra-low illumination CMOS |
| Min.illumination | Color:0.1Lux @(F1.2,AGC ON),0 LUX with IR Black/white:0.01 Lux @(F1.2,AGC ON),0 LUX with IR | | Color:0.01Lux @(F1.2,AGC ON),0 LUX with IR Black/white:0.01 Lux @(F1.2,AGC ON),0 LUX with IR | |
| Shutter | 1/50(1/60)s - 1/10,000s | | | |
| Lens | HD professional lens 3.6mm@ F1.8 (6mm) | | | |
| Lens mount | M12 | | | |
| Day/night | Support IR-CUT | | | |
| compression | | | | |
| video compression | H.264 HighProfile, JPEG snapshot | | | |
| bite rate | 32 Kbps~6Mbps | | | 32 Kbps~8Mbps |
| audio compression | G.711a | | | |
| image | | | | |
| Max.imagereolution | 1280*720 | 1280*960 | 1920*1080 | |
| Frame rate | 50Hz:25fps (1280*720) 60Hz:30fps (1280*720) | 50Hz:25fps (1280*960),(1280*720) 60Hz:30fps (1280*960), 25fps(1280*720) | 50Hz:25fps (1920*1080),(704*576) 60Hz:30fps (1920*1080),(704*480) | |
| Image setting | Saturation, brightness and contrast are adjustable through IE browser or client. | | | |
| network | | | | |
| storage | local SD card storage(optional),network storage | | | |
| intelligent alarm | Motion detection, video loss, cable break, IP address conflicts | | | |
| protocol | TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP (HTTPS,SIP,802.1x,IPv6) | | | |
| basic | anti-flicker, dual-stream, heartbeat, password protection | | | |
| interface | | | | |
| net interface | One RJ45 10M/100M | | | |
| Audio input | No | 1ch 3.5mm JACK | | |
| general | | | | |
| Working condition | -10℃~60℃, humidity less than 90%(non-condensing) | | | |
| Power supply | DC12V±10% | | | |
| Protection range | IP66 | | | |
| IR distance | IR5:10-20meters; | | | |
| dimension | 64.8mm*148mm | | | |
| weight | About 390g | | | |