

## EU2 IR Waterproof Box IP Camera Series



### Model:

IPC-EU25110PE-IR5(Hi3518E)    IPC-EU25313PL-IR5

IPC-EU25313PE-IR5(Hi3518E)    IPC-EH25320PL-IR5

### Feature:

- High resolution, image presented vivid and clear.
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring.
- Support various information superimposed (such as: ID、IP、DDNS and so on), convenient to operate
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support dual-stream
- support various mobile long-distance monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support multiple web browsers (IE、Chrome、Firefox、Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF.

## Specification:

Model	IPC-EU25110PE-IR5	IPC-EU25313PE-IR5	IPC-EU25313PL-IR5	IPC-EU25320PL-IR5
<b>Camera</b>				
Image sensor	1/4" OV 9712 CMOS	1/3"AR0130ultra-low illumination CMOS		1/2.8"SONYIMX122 ultra-low illumination CMOS
Min.illumination	Color:0.1Lux @(F1.2,AGC ON),0 LUX with IR Black/white:0.01 Lux @ (F1.2,AGC ON),0 LUX with IR	Color:0.01Lux @(F1.2,AGC ON),0 LUX with IR Black/white:0.01 Lux @ (F1.2,AGC ON),0 LUX with IR		
Shutter	1/50(1/60)s - 1/10,000s			
Lens	HD professional lens 6mm@ F1.8 (4mm)	HD professional lens 6mm@ F1.8 (4mm,8mm,12mm)		
Lens mount	CS			
Day/night	Support IR-CUT			
<b>compression</b>				
video compression	H.264 HighProfile, JPEG snapshot			
bite rate	32 Kbps~6Mbps	32 Kbps~6Mbps		32 Kbps~8Mbps
audio compression	G.711a			
<b>image</b>				
Max.imagereolution	1280*720	1280*960		1920*1080
Frame rate	50Hz:25fps (1280*720) 60Hz:30fps (1280*720)	50Hz:25fps(1280*720) (1280*960) 60Hz:30fps(1280*720) 25fps(1280*960)		50Hz:25fps(1920*1080) 60Hz:30fps(1920*1080)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client.			
<b>network</b>				
storage	local SD card storage(optional),network storage			
intelligent alarm	Motion detection, video loss, cable break, IP address conflicts			
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,IPv6 )			
basic	anti-flicker, dual-stream, heartbeat, password protection			
<b>interface</b>				
net interface	One RJ45 10M/100M			
Audio input	no	1ch 3.5mm JACK		
<b>general</b>				
Working condition	-10°C~60°C, humidity less than 90%( non-condensing)			
Power supply	DC12V±10%			
Protection range	IP66			
IR distance	IR5:50-60meters;			
dimension	182mm*88mm*88mm			
weight	About 660g			