

EV IR Waterproof Box IP Camera Series



Model:

IPC-EV25110PE-IR5, IPC-EV25313PE-IR5

Feature:

- High resolution, image presented vivid and clear.
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring.
- Support various information superimposed (such as: ID、IP、 DDNS and so on), convenient to operate
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support dual-stream
- support various mobile long-distance monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support multiple web browsers (IE、 Chrome、 Firefox、 Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、 central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF.

specification

model	IPC-EV25110PE-IR5	IPC-EV25313PE-IR5
camera		
image sensor	1/4" OV 9712 CMOS	1/3"AR0130 ultra-low illumination CMOS
min.illumination	Color:0.1Lux @(F1.2,AGC ON),0 LUX with IR Black/white:0.01 Lux @(F1.2,AGC ON),0 LUX with IR	Color :0.01Lux @(F1.2,AGC ON),0 LUX with IR Black/white 0.001 Lux @(F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s -1/10,000s	
lens	HD professional lens 6mm@ F1.8 (4mm,8mm,12mm)	
Lens mount	CS	
Day/night	Support IR-CUT	
compression		
video compression	H.264 HighProfile, JPEG snapshot	
bite rate	32 Kbps~6Mbps	
audio compression	G.711a	
image		
Max.image reolution	1280*720	1280*960
frame rate	50Hz:25fps (1280*720) 60Hz:30fps (1280*720)	50Hz:20fps (1280*960),25fps(1280*720) 60Hz:20fps (1280*960),25fps(1280*720)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client.	
network		
storage	local SD card storage(optional),network storage	
intelligent alarm	Motion detection, video loss, cable break, IP address conflicts	
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP(HTTPS,SIP ,802.1x,IPv6)	
basic	anti-flicker, dual-stream, heartbeat, password protection	
interface		
net interface	One RJ45 10M/100M	
general		
Working condition	-10℃~60℃, humidity less than 90%(non-condensing)	
Power supply	DC12V±10%	
Power consumption	IR3:6W MAX;	
Protection range	IP66	
IR distance	IR3:50-60 meters;	
dimension	90mm*172mm	
weight	About460g	