

## EZ IR Waterproof Box IP Camera Series



### Model:

IPC-EZ5110PL-IR3,IPC-EZ5313PL-IR3,IPC-EZ5120PL-IR3,IPC-EZ5320PL-IR3

### Feature:

- Lens:2.8mm-12mm variable.
- High resolution, image presented vivid and clear.
- Support automatic color change/IR-CUT,achieving day and night non-stop monitoring.
- Support various information superimposed (such as: ID、IP、DDNS and so on), convenient to operate
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support dual-stream
- support various mobile long-distance monitoring (iPhone,Windows Mobile, BlackBerry,Symbian, Android)
- Support multiple web browsers (IE、Chrome、Firefox、Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、 central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF
- Support multiple cloud technology,realising network

penetration, front&rear-end connection, alarm message sent to mobile etc.

## specification

model	IPC-EZ5110PL-IR3	IPC-EZ5313PL-IR3	IPC-EZ5320PL-IR3	IPC-EZ5120PL-IR3
<b>camera</b>				
Image sensor	1/4" OV 9712 CMOS	1/3"AR0130 ultra-low illumination CMOS	1/2.8"SONYIMX222 ultra-low illumination CMOS	1/2.7" OV CMOS
Min.illumination	Color 0.1Lux @ (F1.2,AGC ON),0 LUX with IR Black/white 0.2 Lux @ (F1.8,AGC ON),0 LUX with IR	Color 0.01Lux @ (F1.2,AGC ON),0 LUX with IR Black/white 0.001Lux @ (F1.2,AGC ON),0 LUX with IR		Color 0.6Lux @ (F1.2,AGC ON),0 LUX with IR Black/white 0.08 Lux @ (F1.2,AGC
Shutter	1/50(1/60)s -1/10,000 s			
Lens	HD professional lens 2.8mm-12mm			
Lens mount	ϕ 14			
Day/night	Support IR-CUT			
<b>compression</b>				
video compression	H.264 HighProfile, JPEG capture			
bite rate	32 Kbps~6Mbps	32 Kbps~6Mbps	32Kbps~8Mbps	32Kbps~8Mbps
audio compression	G.711a			
<b>image</b>				
Max.imagereolution	1280*720	1280*960	1920*1080	1920*1080
Frame rate	50Hz: 25fps (1280*720) 60Hz: 30fps (1280*720)	50Hz: 25fps(1280*720) (1280*960) 60Hz: 30fps (1280*720)  25fps(1280*960);	50Hz: 25fps(1920*1080) (1280*720) 60Hz: 30fps(1920*1080) (1280*720)	50Hz: 25fps(1920*1080) (1280*720) 60Hz: 30fps(1920*1080) (1280*720)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client.			
<b>network</b>				
intelligent alarm	Motion detection, video loss, cable break, IP address conflicts			
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,IPv6 optional)			
basic	anti-flicker, dual-stream, heartbeat, password protection			
<b>interface</b>				
net interface	1*RJ45 10M/100M			
Audio interface	1ch 3.5mm audio input			
<b>general</b>				
Working condition	-10℃~60℃, humidity less than90%( non-condensing)			
Power supply	DC12V±10%			
Power consumption	6W MAX;			
Protection range	IP66			
IR distance	"IR3":30-40meters;			
dimension	306mm*118mm*102mm			
weight	1100g			