

# 1080P HD Coaxial Video Camera Module

## 一、 Product Picture



## 二、 Model

**HTG-5020PL-H**

## 三、 Parameters

| Specifications            | HTG-5020PL-H                                                                                                                     |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Sensor                    | 1/2.7 inch F02sensor                                                                                                             |
| Video Resolution          | PAL/NTSC : 1920*1080                                                                                                             |
| Minimum Illumination      | color: 0.1Lux@ (F1.2, AGC ON) , 0Lux with IR                                                                                     |
|                           | Black & White: 0.01Lux@ (F1.2, AGC ON) , 0Lux with IR                                                                            |
| Photosensitive Resistance | 1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT, infrared lamp linkage |
| Shutter                   | 1/50(1/60) seconds to 1/10,000 seconds                                                                                           |
| Day and Night Function    | Support IR-CUT                                                                                                                   |
| Lens Parameters           | C/CS interface, M12 lens optional                                                                                                |
| Synchronous Mode          | inter-sync                                                                                                                       |
| Noise-signal Ratio        | >58dB                                                                                                                            |
| Temperature and Humidity  | - 10 °C ~ 60 °C, humidity is less than 90% (no condensation)                                                                     |
| Power                     | DC12V±10%                                                                                                                        |
| Consumption               | <5W                                                                                                                              |
| Size                      | Standard 32*32 positioning hole, compatible with 38*38 hole                                                                      |
| Remarks                   | Can access to the AHD/TVI/CVI/CVBS backend, switch signal system through shorting out                                            |

|  |        |
|--|--------|
|  | wires. |
|--|--------|