

IPC-EH5320PL-IR3



Model

IPC-EH5320PL-IR3

-support IR-CUT

Feature:

- Introduce SONY ultra-low illumination CMOS sensor
- High resolution, presenting vivid and clear pictures.
- Support automatic color change/IR-CUT,realising day&night non-stop monitoring.
- Support various information superimposed (such as: ID、 IP、 DDNS and so on), convenient to operate
- Introduce advanced H. 264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support dual-stream
- support various mobile long-distance monitoring (iPhone,Windows Mobile, BlackBerry,Symbian, Android)
- Support multiple web browsers (IE、 Chrome、 Firefox、 Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、 central management software MYEYE, providing SDK development
- support HVR/NVR connection, conform to ONVIF.

specification

model	IPC-EH5320PL-IR3
camera	
Image sensor	1/2.9" SONY IMX322 ultra-low illumination CMOS
Min. illumination	Color:0.01Lux @(F1.2, AGC ON), 0 LUX with IR Black/white:0.01 Lux @ (F1.2, AGC ON), 0 LUX with IR
Shutter	1/50(1/60)s - 1/10,000 s
Lens	HD professional lens 6mm@ F1.8 (3.6mm, 8mm, 12mm)
Lens mount	CS
Day/night	Support IR-CUT
compression	
video compression	H.264 HighProfile, JPEG snapshot
bite rate	100 Kbps~8Mbps
image	
Max. image reolution	1920*1080
Frame rate	50Hz:25fps(1920*1080) (1280*720) 60Hz:30fps(1920*1080) (1280*720)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client.
Network	
Storage	Local SD card storage (optional) , Network storage
Intelligent alarm	Motion detection, video loss, cable break, IP address conflicts
protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP (HTTPS, SIP , 802.1x, IPv6)
basic	anti-flicker, dual-stream, heartbeat, password protection
interface	
Network interface	One RJ45 10M/100M
general	
Working condition	-10℃~60℃, humidity less than 90%(non-condensing)
Power supply	DC12V±10%
Power consumption	IR3:6W MAX;
Protection range	IP66
IR distance	IR3:30-40 meters;
dimension	200mm*92mm*75mm
Working condition	500g