



**Model**

IPC-EJ5320PL-IR2

**Features**

- High resolution, clear and smooth image.
- Support automatic turn color to black/IR - CUT, day and night monitoring
- Support all types of superposition of information (such as ID, IP, DDNS server, etc.), easy to use
- Using advantage H.264 High profile video compression,very low bitrate and high definition image.
- Support dual stream
- Support (iPhone, Android)
- Support (IE、Chrome、Firefox、Safari)
- Support auto iris and electronic shutter,
- Provide web,CMS and center manage software (MYEYE)and SDK for second development.
- Support connection with HVR/NVR and Onvif
- Support Onvif

**Specification**

Model	IPC-EJ5313PL-IR2
Camera	
Image sensor	1/2.9" SONY IMX322 Low Illumination CMOS Sensor
Low Illumination	Color:0.01Lux @(F1.2,AGC ON),0 LUX with IR B/W:0.01 Lux @ (F1.2,AGC ON),0 LUX with IR
Electronic Shutter	1/50(1/60)S~ 1/10,000S
Lens	3.6mm@F1.8(6mm,8mm,12mm optional)
Lens mount	M12
Day/Night	Support IR-CUT
Compression Standard	

Video Compression	H.264 MianProfile, JPEG snapshot
Bit rate	32Kbps~8Mbps
Audio Compression	G.711a
<b>Image</b>	
Max.Image Resoultion	1920*1080
Frame rate	50Hz:25fps(1920*1080),(704*576) 60Hz:30fps(1920*1080),(704*480)
Image Setting	Saturation,Brightness,Contrast adjustable through client software or Web server
<b>Network,</b>	
Storage	Micro SD card and Network storage
Intelligent Alarm	Motion detect,Video loss,Network disconnention,IP address conflict
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP (HTTPS,SIP ,802.1x,IPv6 optional)
Basic	Anti-flicker,dual stream,heartbeat,password proteciotn
<b>Interface</b>	
Net interface	1 * RJ45 10M/100M
Audio interface	1ch 3.5mm audio input
<b>General</b>	
Operating Condition	-10℃~60℃ , Humidity 90% or less(non-condensing)
Power supply	DC12V±10%
Power consumption	“IR3”:6W MAX;
Protection Range	IP66
IR distance	“IR2”:20-30 M;
Dimension	200mm*84mm*72mm
Weight	300g