

IPC-HR5313PE-IR2



Feature:

- High resolution 960P, image presented vivid and clear
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring
- Support various information superimposed (such as: ID、IP、DDNS and so on)
- Advanced video compression, achieving ultra-low bit-rate, superb high-definition picture quality
- support various mobile long-distance monitoring (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support multiple web browsers (IE、Chrome、Firefox、Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、central management software MYEYE, providing SDK development.
- Support HVR/NVR connection, support ONVIF standard


Scenarios:

Apply for road, warehouse, underground parking lot, bar, pipeline and somewhere where require HD images but with dark light and poor sunshine.

Model:

IPC-HR5313PE-IR2

Dimension:



Parameters:

Model	IPC-HR5313PE-IR2
Camera	
Image sensor	1/3" CMOS sensor
Min. illumination	Color 0.01Lux @(F1.2, AGC ON), 0 LUX with IR B/W 0.001 Lux @(F1.2, AGC ON), 0 LUX with IR
Shutter	1/50(1/60)s to 1/10,000s
Lens	HD professional lens 3.6mm @ F1.8 (6mm option)
Lens mount	M12
Day/night	Support IR-CUT
Compression	
Video compression	H.264 HighProfile, JPEG snapshot
Bite rate	32 Kbps~6Mbps
Audio compression	G.711a
Image	
Max. image resolution	1280*960
Frame rate	50Hz: 20fps(1280*960), 25fps(1280*720) 60Hz: 20fps(1280*960), 25fps(1280*720)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client software.
Network	
Storage	Network storage
Intelligent alarm	Motion detection, video loss, cable break, IP address conflicts
protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP (HTTPS, SIP, 802.1x, IPv6 option)
Basic	anti-flicker, dual-stream, heartbeat, password protection
Interface	
Network interface	1* RJ45 10M/100M adaptive ethernet port
Audio interface	No
General	
Working condition	-10°C~60°C, humidity less than 90% (non-condensing)
Power supply	DC12V±10%
Protection range	IP66
IR distance	"IR2": 20-30 meters
Dimension	Φ 110mm*88mm
Weight	约 202g