

## IPC-HS5110PE-IR1 IP Camera



### Model :

IPC-HS5110PE-IR1

### Feature:

- High resolution 720P, image presented vivid and clear
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring
- Support various information superimposed (such as:ID、 IP、 DDNS and so on)
- Advanced video compression, achieving ultra-low bit-rate, superb high-definition picture quality
- support various mobile long-distance monitoring(ios, Android)
- Support multiple web browsers(IE、 Chrome、 Firefox、 Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、 central management software MYEYE, providing SDK development.
- Support HVR/NVR connection, support ONVIF standard

**Specificatio:**

Model	IPC-HS5110PE-IR1
Image sensor	1/4" CMOS sensor
Min.illumination	Color 0.1Lux @(F1.2,AGC ON),0 LUX with IR B/W 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s to 1/10,000 s
Lens	HD professional lens3.6mm@ F1.8 (6mm option)
Lens mount	M12
Day/night	Support IR-CUT
Video compression	H.264 main Profile, JPEG snapshot
Bite rate	32 Kbps~6Mbps
Audio compression	G.711a
Max.image reolution	1280*720
Frame rate	50Hz:25fps(1280*720) 60Hz:25fps(1280*720)
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client software.
Storage	Network storage
Intelligent alarm	Motion detection, video loss, cable break, IP address conflicts
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP(HTTPS,SIP ,802.1x,IPv6 option)
Basic	anti-flicker, dual-stream, heartbeat, password protection
Network inferface	1 * RJ45 10M/100M adaptive ethernet port

Audio Interface	No
Working condition	-10°C~60°C, humidity less than 90%( non-condensing)
Power supply	DC12V±10%
Power consumption	6W MAX
Protection rang	IP66
IR distance	“IR1”:10-20 meters;
Dimension	∅ 93mm*68mm
Weight	300g