

IPC-EW5313PL-IR3
1.3 million low illumination wireless IP Camera



Feature:

- HD 720P resolution, image clarity, detail;
- Minimum illumination: 0.1Lux @ (F1.2,AGC ON),0 LUX with IR;
- Support electronic switch day/night;
- Support SD card storage;
- Support two-way audio
- Support WIFI;
- support all types of mobile remote monitoring (iOS, Windows Mobile, BlackBerry, Symbian, Android);
- Multi-browser access (IE, Chrome, Firefox, Safari);
- Support web, CMS, center platform management software MYEYE, provide SDK Development.

Model:

IPC-EW5313PL-IR3

Parameters:

Model	IPC-EW5313PL-IR3
Network camera	
Sensor	1/3 " Aptina low illumination CMOS sensor
Minimum illumination	Color 0.01Lux @(F1.2,AGC ON),0 LUX with IR Black & White 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s to 1/10,000s
Lens	HD professional lens 6mm@ F1.8 (4mm,8mm,12mm)
Lens Interface	CS
Day and night	Support IR-CUT
Compression Standard	
Video	H.264 High Profile, JPEG snapshot
output rate	32 Kbps~6Mbps
audio	G.711a
Image	
Max. image size	1280*960
Frame Rate	50Hz:25fps(1280*720) , (1280*960) 60Hz:30fps(1280*720) ,25fps(1280*960)
Image Settings	Saturation, brightness and contrast can be adjusted through IE or Client
Network functions	
Storage	Support local MicroSD and network storage
WIFI	Support
Intelligent Alarm	Motion detection, video loss, cable break, IP address conflict
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,IPv6Optional)
Other	Anti-flicker, dual-stream, heartbeat, password protection
Interface	
Communication	1*RJ45 10M/100M
General Specifications	
temperature and humidity	-10℃~60℃, humidity less than 90% (non-condensing)
Power supply	DC12V±10%
Power Consumption	"IR3":8W MAX;
Protection class	IP66
Infrared radiation	"IR3":30-40m;