

**JF-ADVR7004T-H**  
**1 SATA 4ch Analog HD DVR**



**Features:**

- Support AHD-H series front-end real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

**Model:**

**JF-ADVR7004T-H**

**Interface:**

**Parameter:**

	Model	JF-ADVR7004T-H	
System	Main processor	Huawei Hi 3531	
Video	Video codec	H.264(High Profile);	
	Encode	4*AHD-H	
	Decode	4*AHD-H	
Video	Multi-mode input	Pure Analog: 4*AHD-H; 4*AHD-M; Mixed: 2*AHD-H(analog)+2*1080P(network); 4*AHD-M (analog) +4*720P (network) ; Pure Network: 4*1080P; 20*960H; 1*1080P+8*720P;	
	Audio compression	G.711A	
Audio	Intercom	support	
	Record mode	Manual>alarm>motion detection>timing	
Recording and Playback	Playback Channels	4	
	Space occupation	1080P: 20G~30G/ day*channel 720P: ~20G/ day*channel 960H: 12~20G/ day*channel audio: 691.2M/ day*channel	
Storage and backup	Backup mode	Network backup、USB HDD, USB writer、SATA writer	
	Video input	4 BNC	
Interface	Video output	1ch VGA,1ch HDMI	
	Audio input	4ch RCA	
	Audio output	1ch RCA	
	Alarm input	0	
	Alarm output	0	
	Network interface	RJ45 10M/100M Adaptive Ethernet port	
	PTZ control	One RS485; support multiple PTZ protocols	
	USB	2 USB ports	
	Hard disk	1 SATA ( Each maximum support 4T )	
	Wireless	3G、WIFI(expand via USB)	
	Other	Power	12V/2A
		dimension	255mm(length)* 236mm(width)* 44mm(height)