

JF-ADVR7008F-M
4 SATA 8ch Analog HD DVR



Features:

- Support AHD-M series front-end real-time encoding;
- Support VGA, HDMI 1080P full HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

JF-ADVR7008F-M

Interface:

Parameter:

	Model	JF-ADVR7008F-M
System	Main processor	Huawei Hi 3531
Video	video codec	H.264(High Profile);
	Encode	8*AHD-M
	Decode	8*AHD-M
Video	Multi-mode input	Pure Analog: 8*AHD-M; 8*AHD-L; Mixed: 4*AHD-M(Analog)+4*720P(Network); 8*AHD-M (Analog) +8*720P (Network) Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H
	Audio compression	G.711A
Audio	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Recording and Playback	Playback Channels	8 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	8 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	8ch RCA
	Audio output	1ch RCA
	Alarm input	16
	Alarm output	4
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	One RS485, one RS232; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	4 SATA (Each maximum support 4T)
Other	Wireless	3G、WIFI(expand via USB)
	Power	12V/6A
Other	dimension	440mm(length)* 400.5mm(width)* 60mm(height)