

JF-ADVR7016DA-LM
2 SATA 16ch Analog HD DVR



Features:

- Support AHD-M series front-end real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE、Chrome、Firefox、Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

JF-ADVR7016DA-LM

Interface:

Parameter:

	Model	JF-ADVR7016DA-LM
System	Main processor	Hi 3531
	video codec	H.264
Video	Encode	16*1080N@15fps/16*AHD-M
	Decode	1*1080N@15fps/1*AHD-M
	Multi-mode input	PureAnalog:16*1080N; 16*AHD-M;8*AHD-M; 16*AHD-L; Mixed: 4*AHD-M(analog)+4*720P (network) ; 8*AHD-M(analog)+8*720P (network) Pure Network: 1*1080P+8*720P; 4*1080P; 20*960H;
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel 720P: ~20G/ day*channel audio: 691.2M/ day*channel
	Backup mode	Network backup、USB HDD, USB writer、SATA writer
Interface	Video input	16 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	6ch RCA
	Audio output	1ch RCA
	Alarm input	4
	Alarm output	1
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2 SATA (Each maximum support 6T)
Other	Wireless	3G、WIFI(expand via USB)
	Power	12V/4A
	dimension	350mm(length)* 296mm(width)* 44mm(height)