

**JF-ADVR7808R-EL(HDMI)
1 SATA 8ch Analog HD DVR**



Features:

- Support D1 series front-end real-time encoding,AHD-L series front-end non-real-time encoding;
- Support VGA, TV,HDMI output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

JF-ADVR7808R-EL(HDMI)

Interface:

Parameter:

| | Model | JF-ADVR7808R-EL(HDMI) |
|------------------------|-------------------|---|
| System | Main processor | Huawei Hi 3520D |
| Video | video codec | H.264(High Profile); |
| | Encode | 8*D1 /8*AHD-L@12fps |
| | Decode | 1*D1 /2*AHD-L@12fps |
| Audio | Multi-mode input | Pure Analog: 8*AHD-L: 8*D1; 8*HD1; Mixed: 2*D1(analog)+1*720P (network) +1* 1080P(network); Pure Network: 4*1080P; 4*720P; 8*720P; 8*1080P; 1*1080P |
| | Audio compression | G.711A |
| Recording and Playback | Intercom | support |
| | Record mode | Manual>alarm>motion detection>timing |
| Storage and backup | Playback Channels | 2 (pure local input mode) |
| | Space occupation | 960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel |
| Interface | Backup mode | Network backup、USB HDD, USB writer、SATA writer |
| | Video input | 8 BNC |
| | Video output | 1ch VGA, 1ch TV,1ch HDMI |
| | Audio input | 1ch RCA |
| | Audio output | 1ch RCA |
| | Alarm input | NO |
| | Alarm output | NO |
| | Network interface | RJ45 10M/100M Adaptive Ethernet port |
| | PTZ control | NO |
| | USB | 2 USB ports |
| | Hard disk | 1 SATA (Each maximum support 6T) |
| | Wireless | No |
| Other | Power | 12V/2A |
| | dimension | 210mm(length)* 200mm(width)* 49mm(height) |