

JF-VS7124D



Features:

- JF-VS7124D is a storage server that general features such as management server,storage,extensibility are integrated
- Intel to power technology:support super thread、third string
- Support virtualization device input/output(VT-d);
- Inner core speeds up 2(Turbo Mode)
- Integrated memory controller(IMC):Move it from CS to CPU,support multiple channels DDR3 memory,the delay of memory read can be reduced greatly,memory bandwidth can also improve up to triple;
- High availability:match to processor Hyper Threading,support multiple threads and missions;
- Support RAID 0、1、5、10、50 modes,meet the security of System;
- Intel and 1000M network adaptor,support link to combine and bound the function of redundancy;
- Advanced the design of case,adopt intelligent rejection of heat system,easy to reduce noise pollution,create a constant temperature,prevent electromagnetic radiation fully, against interference,prevent static electricity(EMI),apply to multiple application environment;
- Flexible configuration and architecture,disk and server are combined perfectly;
- Web、CMS、center platform management software MYEYE、provide SDK development;
- Meet 128ch720P / 64ch 1080P to store 、manage and forward

Model:

JF-VS7124D

Parameters:

	Model	JF-VS7124D
System	Main processor	Xeon
	Operating	WINDOWS/LINUX
	Memory/flash	4GB DDR3 1600MHZ, Max:32GB
	Display interface	VGA/DVI/HDMI
	Network	Intel dual gigabit Ethernet
	Built-in disk	1* 500G SATA 6.0Gb/s 2.5 inch
	Expand disk	24* 3.5 inch (max:96T)
		Independent disk shelf,support hot plug,and SATA3Gb/s Up to 4TB for each disk
	RAID	Raid0、1、5、6、10、50、JBOD,hot standby
	USB	5*USB2.0
	Communication	1*RS232
	Audio port	N/A
	Power supply	1+1 redundancy 860W(220V) 80+/hot plug
	Install system	Windows 2008 Server R2
	Support system	Linux/WES7
Alarm card	Support 16ch input and 8ch output	
Button	Power switch,reset	
LED	Preposition:1*power indictor,2*network indictors, 1*built-in disk indicator,1*built-in fan indictors Back: 2*network indictors,shel: 2*disk lights	
Dimension	Rack mounted 4U,433x660x178mm	
Temperature	5°C to 40°C/41°F to 104°F	
Humidity	5% ~ 95% no frosting	
Weight	24KG	
	Input voltage	100~240V, 47~63HZ