

## Manual Focus IP Camera EQB Series



### Model :

IPC-EQB5313PL-IR3、IPC-EQB5320PL-IR3

### Feature:

- High resolution 960P/1080P, image presented vivid and clear
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring
- Support various information superimposed (such as:ID、IP、 DDNS and so on)
- Advanced video compression, achieving ultra-low bit-rate, superb high-definition picture quality
- support various mobile long-distance monitoring(ios, Android)
- Support multiple web browsers(IE、 Chrome、 Firefox、 Safari)
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting、 central management software MYEYE, providing SDK development.
- Support HVR/NVR connection, support ONVIF standard

### Specifictio:

|       |                   |                   |
|-------|-------------------|-------------------|
| Model | IPC-EQB5313PL-IR3 | IPC-EQB5320PL-IR3 |
|-------|-------------------|-------------------|

|                     |   |  |
|---------------------|---|--|
| Image sensor        | 1/3" CMOS sensor  | 1/2.8" Ultra-low illumination CMOS sensor        |
| Min.illumination    | Color :0.01Lux @(F1.2,AGC ON),0 LUX with IR<br>Black/white 0.001 Lux @(F1.2,AGC ON),0 LUX with IR |  |
| Shutter             | 1/50(1/60)s to 1/10,000 s   |  |
| Lens                | 3.6mm—10mm Manual Focus zoom lens   |  |
| Lens mount          | M14   |  |
| Day/night           | Support IR-CUT  |  |
| Video compression   | H.264 main Profile, JPEG snapshot   |  |
| Bite rate           | 32 Kbps~6Mbps   | 32 Kbps~8Mbps                                    |
| Audio compression   | G.711a  |  |
| Max.image reolution | 1280*720  | 1920*1080  |
| Frame rate          | 50Hz:25fps(1280*960),(1280*720)<br>60Hz:30fps(1280*960), (1280*720)                               | 50Hz:25fps (1920*1080)<br>60Hz:30fps (1920*1080) |
| Image setting       | Saturation, brightness and contrast are adjustable through IE browser or client software.         |  |
| Storage             | Network storage   |  |
| Intelligent alarm   | Motion detection, video loss, cable break, IP address conflicts                                   |  |
| protocol            | TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP(HTTPS,SIP ,802.1x,IPv6 option)                          |  |
| Basic               | anti-flicker, dual-stream, heartbeat, password protection   |  |
| Network inferface   | 1 * RJ45 10M/100M adaptive ethernet port  |  |
| Audio Interface     | 1ch 3.5mm audio input   |  |
| Working             | -10°C~60°C , humidity less than 90%( non-condensing)  |  |

|                   |                     |
|-------------------|---------------------|
| condition         |                     |
| Power supply      | DC12V±10%           |
| Power consumption | "IR3":6W MAX;       |
| Protection rang   | IP66                |
| IR distance       | "IR1":30-40 meters; |
| Dimension         | Φ 76mm*296mm        |
| Weight            | About700g           |