


## HANGZHOU XIONGMAI TECHNOLOGY CO.,LTD

## NBD7804R-F(HDMI)

## Feature:

- ➤ Support VGA, HDMI 1080P full HD output simultaneously;
- ➤ Support ONVIF; access third party
- ➤ Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- ➤ Support web, CMS, center platform management software MYEYE, provide SDK development;
- ➤ Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.);



Service QQ: 4008553199

Hot line: 4008553199

Parameters:

Model: NBD7804R-F(HDMI)

	Model	NBD7804R-F(HDMI)
System	Main processor	Hi3520D
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/8
	Video input (IP)	4*1080P/8*960P/8*D1
Video	Video standards	PAL(625TVL,50f/s); NTSC(525TVL,60f/s)
	Video compression	H.264
	Display quality	Max 1920*1080
	Playback quality	1080P/960P /D1
	Decode	1*1080P/1*960P/4*D1
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	Unsupport
Record & playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local payback	1*1080P/1*960P/4*D1
	Search mode	Search by Time/Calendar/Event/Channel
Chamana	Space occupation	Video: CIF 4~5G/day*channel, D1 8~10G/day*channel; 960H 12G~20G/day*channel
Storage & Backup		720P 20~30G/day*channel; 1080P ~40G/day*channel; Audio: 691.2M/day*channel
	Record storage	HDD 、Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
	Video output	1ch VGA、1 ch HDMI HD Output
External interface	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port
	USB interface	2*USB2.0 ports
	HDD	1 SATA(Up to 8TB for each disk)
	PTZ control	Control PTZ device by network
General	ONVIF	Support
	Power supply	12V/2A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0 $^{\circ}$ C- $+$ 55 $^{\circ}$ C , Humidity:10% $-$ 90%RH , Atm:86kpa $-$ 106kp
	Dimension	136mm(L)*81mm(W)
	Weight	Around 95g