



NBD7904T-PL-XPOE



Feature:

- Support H.265X encoding, ultra-low bitrates;
- Support VGA, HDMI full HD output simultaneously;
- Support 4*XPOE+4*IPC
- XPOE network port power supply
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP),easy to monitor remotely

Specification:

	Model	NBD7904T-PL-XPOE
System	Main processor	HI3520DV300
Interface	Preview	1/4
Video	Codec	H.265X
	Monitor quality	VGA(1080P at most);HDMI(1080P at most)
	Video Input	4*1080P (XPOE); 4*1080P(XPOE)+4*1080P(IPC)
	Playback	4*1080P; 2*1080P
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	N/A
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch/2ch
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	4*XPOE+4*IPC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	48V/1.5A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	195mm*85mm
	Weight	148g