


## NBD8008T-Q 8ch 4.0M H.256 NVR Board

## Feature:

- ➤ Support HDMI VGA 4K output;
- ➤ Support 180° 360° VR;
- ➤ Support web, CMS, center platform management software MYEYE, provide SDK development;
- ➤ Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- ➤ Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.);



Customer service QQ (enterprise): 4008553199

Hot line: 4008553199

Model: NBD8008T-Q

	Model	NBD8008T-Q
System	Main processor	Hi3798M
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/8/16
Video	Video input (IP)	4*4K/4*5M/8*4M/4*3M/12*1080P/16*960P
	Access bandwidth	72Mbps
	Forwarding bandwidth	72Mbps
	Video compression	H.265/H.264
	Display quality	Max 4K
	Playback quality	4K/5M/4M/3M/1080P/960P
	Decode	1*4K/2*5M/2*4M/4*3M/4*1080P/4*960P
	VR	support
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	Unsupport
	Recording mode	Manual>Alarm>Dynamic Detection>Timing
Record	Local payback	1*4K/2*5M/2*4M/4*3M/4*1080P/4*960P
&	Search mode	Search by Time/Calendar/Event/Channel
playback	Record storage	HDD、Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch HDMI HD output
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port+4ch WIFI
	USB interface	2*USB2.0 ports
	HDD	2 SATA(Up to 8TB for each disk)
	ESATA	No
	Serial interface	No
Other	ONVIF	Support
	Power supply	12V/4A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0 $^\circ\mathrm{C}$ - $+$ 55 $^\circ\mathrm{C}$ , Humidity:10% $-$ 90%RH , Atm:86kpa $-$ 106kp
	Dimension	164mm*85mm
	Weight	A total of about 100g