

NVR6908T-PL/Poe



Features:

- Support multiple high-definition network camera access; up to 1080P
- Support TV VGA HDMI output simultaneously;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3G,WIFI, IP searches, Alarm Center,etc.);
- Support ONVIF ;
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely,built-in ARSP,remote monitoring by one step

Parameters:

	Model	NVR6908T-PL	NVR6908T-PL/Poe
System	Main processor	Hi3520D	
	Operating system	Embedded Linux	
Interface	Operator interface	16-bit true color graphic menu operation interface,support mouse operation	
	Preview	1/4/8	
Audio& video	Video input	8/4* 1080P,8/4*720P	
	Decode	H.264	
	Monitor quality	Max 1920*1080	
	Playback quality	1080P/720P	
	Standard	Video: PAL, NTSC; Audio:G.711A	
	Motion detection	Depend on camera)	
Video playback	Intercom	Unsupport	
	Record mode	Manual>Alarm>Dynamic Detection>Timing	
	Local playback	2*1080P,4*720P	
	Search mode	Search by time/calendar/event/channel	
	Record storage	HDD,Network	
External interface	Backup mode	Network backup, USB hard disk, USB burner, SATA burner	
	Video out	1 ch BNC, 1ch VGA, 1ch HDMI	
	Audio I/O	0/1	
	Alarm I/O	0/0	
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port ,4 POE ports Support POE power supply (optional POE module)	
	USB interface	2*USB2.0 ports	
General	HDD	1 SATA(Up to 6TB for each disk)	
	PTZ control	Control PTZ device by network	
	ONVIF	Support	
	GB28181	Optional	
	Work environment	Temperature:0℃-+55℃ , Humidity:10%-90%RH , Atm:86kpa-106kp	
	Weight	Around 1.2KG	
	Power supply	12V/3A	12V/3A,48V/1.5A
	power consumption	<10W (without HDD)	
Dimension	255(L)* 236mm(W)* 44mm(H)		

Model:

NVR6908T-PL/Poe

Interface:

