

**NVR7024F-P**




**Features:**

- Support multiple high-definition network camera access; up to 1080P
- Support VGA, HDMI 1080P full HD output simultaneously;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.);
- Support ONVIF ;
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely, built-in ARSP, remote monitoring by one step

**Model:**

**NVR7024F-P**

**Interface:**



**Parameters:**

	Model	NVR7024F-P
System	Main processor	Hi3535
	Operating system	Embedded Linux
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/8/16/24/32
Audio & video	Video input	8*5M/16*3M/ 24、16/8*1080P/32*960P/16*720P
	Decode	H.264
	Monitor quality	Max 1920*1080
	Playback quality	5M/3M/1080P/960P/720P
	Standard	Video: PAL, NTSC; Audio: G.711A
	Motion detection	Depend on camera
	Intercom	Support
Video playback	Record mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	2*5M/4*3M/4、8、8*1080P/8*960P/16路720P
	Search mode	Search by time/calendar/event/channel
	Record storage	HDD, Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video out	1ch VGA, 1ch HDMI
	Audio I/O	1/1
	Alarm I/O	16ch/4ch
	Network interface	1*RJ45 10M/100M/1000M adaptive Ethernet port
	PTZ control	Control PTZ by network
	USB interface	2*USB2.0, 1USB3.0 ports
	HDD	4*SATA (Max 6T for each), 1*ESATA
Other interface	1*RS232	
General	ONVIF	Support
	GB28181	Optional
	Work environment	Temperature: 0°C - +55°C, Humidity: 10% - 90%RH, Atm: 86kpa - 106kpa
	Weight	Around 4KG
	Power supply	12V/6A
	Dimension	440mm(L)* 400.5mm(W)* 60mm(H)