

NVR7804R-F




Features:

- Support multiple high-definition network camera access;
- up to 1080P
- Support VGA, HDMI 1080P full HD output simultaneously;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3g,wifi,IP searches, Alarm Center,etc.);
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely,built-in ARSP,remote monitoring by one step

Model:

NVR7804R-F

Interface:



Parameters:

	Model	NVR7804R-F
System	Main processor	Hi3515C
	Operating system	Embedded Linux
Interface	Operator interface	16-bit true color graphic menu operation interface,support mouse operation
	Preview	1/4
Audio&video	Video input	4*1080P/8*D1
	Decode	H.264
	Monitor quality	Max 1920*1080
	Playback quality	1080P/D1
	Standard	Video: PAL, NTSC; Audio:G.711A
	Motion detection	Depend on camera
	Intercom	Unsupport
Record & Backup	Record mode	Manual>Alarm>Dynamic Detection>TimingDetection>Timing
	Local playback	1*1080P/4*D1
	Search mode	Ssearch by time/calendar/event/channel
	Record storage	HDD, network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video out	1ch VGA
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M ,Adaptive Ethernet port
	PTZ control	Control PTZ by network
	USB	2*USB2.0 ports
General	HDD	1*SATA (Max 6T for each)
	ONVIF	Support
	Work environment	Temperature:0℃-+55℃ , Humidity:10%—90%RH , Atm:86kpa—106kpa
	Weight	Around 0.5KG
	Power supply	12V/2A
	Dimension	210mm (L)* 200mm(W)* 49mm(H)