

NVR7904D-Q/Poe



Features:

- Support multiple high-definition network camera access; up to 4*3M, 4 POE ports Support POE power supply
- Support VGA, HDMI 1080P full HD output simultaneously;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3G,WIFI, IP searches, Alarm Center,etc.);
- Support ONVIF & GB28181;
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely,built-in ARSP,remote monitoring by one step

Parameters:

	Model	NVR7904D-Q/Poe
System	Main processor	Hi3535
	Operating system	Embedded Linux
Interface	Operator interface	16-bit true color graphic menu operation interface,support mouse operation
	Preview	1/4
Audio& video	Video input	4*3M
	Decode	H.264
	Monitor quality	Max 1920*1080
	Playback quality	3M
	Standard	Video: PAL, NTSC; Audio:G.711A
	Motion detection	Depend on camera
	Intercom	Support
Video playback	Record mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	4*3M
	Search mode	Search by time/calendar/event/channel
	Record storage	HDD, Network
	Backup mode	Network backup,USB hard disk,USB burner,SATA burner
External interface	Output interface	1ch VGA, 1ch HDMI
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port , 4 POE ports Support POE power supply
	Audio I/O	1/1
	Alarm I/O	0/0
	USB interface	2*USB 2.0 ports
	HDD	2 SATA(Up to 6TB for each disk)
General	PTZ control	Control PTZ device by network
	ONVIF	Support
	GB28181	Optional
	Work environment	Temperature:0℃-+55℃ , Humidity:10%-90%RH , Atm:86kpa-106kp
	Weight	Around 1.8KG
	Power supply	48V/1.5A
	power consumption	<10W (without HDD)
	Dimension	350mm(L)* 296.4mm(W)* 44mm(H)

Model:

NVR7904D-Q/Poe

Interface: