

NVR7904R-FS



Features:

- Support multiple high-definition network camera access; up to 1080P
- Support VGA hdmi video out
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3g,wifi, IP searches, Alarm Center,etc.);
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Visit remotely,built-in ARSP,remote monitoring by one step

Model:

NVR7904R-FS

Interface:



Parameters:

	Model	NVR7804R-F
System	Main processor	Hi3520D
	Operating system	Embedded Linux
Interface	Operator interface	16-bit true color graphic menu operation interface,support mouse operation
	Preview	1/4/8
Audio&video	Video input	8、4*1080P/8、 4*720P
	Decode	H.264
	Monitor quality	Max 1920*1080
	Playback quality	1080P/720P
	Standard	Video: PAL, NTSC; Audio:G.711A
	Motion detection	Depend on camera
Record & Backup	Intercom	Unsupport
	Record mode	Manual>Alarm>Dynamic Detection>TimingDetection>Timing
	Local playback	2*1080P/4*720P
	Search mode	Ssearch by time/calendar/event/channel
External interface	Record storage	HDD, network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
	Video out	1ch VGA, 1ch HDMI
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M,Adaptive Ethernet port 4 Poe ports,support poe power supply
	PTZ control	PTZ control via network equipment
General	USB	2*USB2.0 ports
	HDD	1 *SATA (Max 6T for each)
	ONVIF	Support
	Work environment	Temperature:0℃ - +55℃ , Humidity:10% - 90%RH , Atm:86kpa - 106kp
	Weight	Around 0.6KG
	Power supply	20V/5A
	Dimension	210mm (L)* 200mm(W)* 49mm(H)