

**NVR8008D-Q**

**Features:**

- Support multiple high-definition network camera access;
- Support HDMI 4K output ;
- Support web, CMS, MYEYE platform, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3g,wifi,IP searches, Alarm Center,etc.);
- Support GB28181 ;
- Support several mobile system (iOS, Android);
- Support multiple web browser access (IE, Chrome, Firefox, Safari);
- More than twenty languages;
- Perfect protection circuit, unique triple watchdog function;

**Model:**
**NVR8008D-Q**
**Interface:**
**Parameters:**

	Model	NVR8008D-Q
System	Main processor	Hi3798M
	Operating system	Embedded Linux
Interface	Operator interface	16-bit true color graphic menu operation interface,support mouse operation
	Preview	1/4/8/16
Audio&video	Video input	4*5M/8*3M/16*960P
	Decode	H.264/H.265
	Monitor quality	Max 4K
	Playback quality	5M/3M/960P
	Standard	Video: PAL, NTSC; Audio:G.711A
	Motion detection	Depend on camera
	Intercom	Usupport
Record & Backup	Record mode	Manual>Alarm>Dynamic Detection>TimingDetection>Timing
	Local playback	2*5M/4*3M/4*960P
	Search mode	Ssearch by time/calendar/event/channel
	Record storage	HDD, network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video out	1ch HDMI
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M ,Adaptive Ethernet port
	PTZ control	Control PTZ device by network
	USB	3*USB2.0 ports
	HDD	2 *SATA(Max 6T for each )
General	ONVIF	Support
	GB28181	Optional
	Work	Temperature:0℃- +55℃ , Humidity:10% — 90%RH , Atm:86kpa— 106kp
	Weight	Around 1.6KG
	Power supply	12V/4A
	Dimension	350(L)* 296.4mm(W)* 44mm(H)