

IPG-53H13PET-S

Features:

- 1/3 " illumination CMOS sensor;
- Main stream:1280*960 (18fps) : 1280*720 (25fps) ;sub-stream: 704*576;352*288
- Support ONVIF; Support Third-party NVR;
- Support for mobile video surveillance(iOS,android);
- Support Web, CMS, platform management software MYEYE,Provide SDK ;
- Support cloud service, network penetration, alarm information pushed to phone ,etc.



Parameters:

Model	IPG-53H13PET-S
System structure	Embedded RTOS,dual-core 32bit DSP(Hi3518E),pure hard compression ,watch dog
Sensor	1.3M 1/3 "low illumination CMOS sensor; color 0.01Lux@F1.2,black/white 0.001Lux@F1.2
Video compression	H.264,support dual stream,AVI;0.1M~6Mbps variable;1~25f/s variable
Image output	Main stream:1280*960 (18fps) : 1280*720 (25fps) ;sub-stream: 704*576;352*288
Other interface	1 external single,1 IR-CUT,support photo resistor input signal and image,IR-CUT,infrared light linkage;an alarm input interface,audio input and output interfaces, working status indicator Interface
Lightning Protection	Power lightning protection,in line with national standards GB/T17626.5,the international standard IEC61000-4-5.
Other function	Support WEB configure,support for OSD,support real-time video transmission, support mobile surveillance,support for mobile detection alarm center after the screen pop-up reminders and linkage;supports JPEG capture;support unified client remote monitoring software,MYEYE platform system applications;provide perfect the SDK development package;
ONVIF	support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC5V
dimension	38mm*38mm
Other	Support POE power supply (optional),-S is neutral generic version, does not accept any custom