

IPG-X131S-S-F36
Features:

- 1.3M 1/3" SC1135 low illumination CMOS sensor
- Support 3D DNR, DWDR;
- Support ONVIF;Support Third-party NVR;
- Support for mobile video surveillance(iOS,android);
- Support Web, CMS, platform management software MYEYE,Provide SDK ;
- Support cloud service, network penetration, alarm information pushed to phone ,etc.


Parameters:

| | |
|-------------------|--|
| Model | IPG-X131S-S-F36 |
| System structure | Embedded RTOS,dual-core 32bit DSP(XM510),pure hard compression ,watch dog |
| Sensor | 1.3M 1/3" SC1135 low illumination CMOS sensor ,color 0.01Lux@F1.2,black/white 0.001Lux@F1.2 |
| Video compression | H.264,support dual stream,AVI;0.1M~6Mbps variable;1~30f/s variable |
| Image output | Main stream: 1280*960,1280*720;sub-stream: 704*576; |
| Shutter | 1/50(1/60)s to 1/10,000s |
| Lens | Frequent 3.6mm M12 Lens |
| Day and night | Support IR-CUT |
| Noise reduction | Support 2D/3D |
| Wide dynamic | Support digital |
| Network interface | 1*RJ45 10/100M adaptive Ethernet port;support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc |
| Singal interface | One photo resistance interface,one IR-CUT interface ,support photo resistance signal and IR-CUT links to IR |
| Auto iris | No |
| SD Card | Unsupport |
| Reliability | Comprehensive lightning protection, in line with national and international standards; 7 * 24 hours 65 °C high temperature stable and reliable testing (including mounted machine testing) |
| Other function | Support OSD,live video transmission,motion detect and IO alarm,front-end storage/playback/download, and center reminder and image linkage,support JPEG capture; united remote client monitoring sofaware 、MYEYE;perfect SDK; |
| ONVIF | Support |
| Mobile monitoring | Support multiple mobile monitoring (iOS, Android) |
| Power | DC12V/2A input, power consumption: ≤3W |
| Dimension | 38mm*38mm |
| Explain | Support POE power supply (optional), not support any custom |