

IPM-50V10PL-WR

Features:

- Supports Wireline、Wi-Fi, a key WPS function;
- Support Micro SD card, up to 32G;
- Support 3D DNR, DWDR;
- Support for mobile video surveillance(iOS,android);
- Support Web, CMS, platform management software MYEYE, Provide SDK ;
- Support cloud service, network penetration, alarm information pushed to phone ,etc.



Parameters:

Model	IPM-50V10PL-WR
System structure	Embedded RTOS, New generation high performance DSP,pure hard compression ,watch dog
sensor	Match and use with ISM-5010PVT-R,color 0.1Lux@F1.2,black/white 0.01Lux@F1.2
Video compression	H.264,support dual stream,AVI;0.1M~6Mpbs variable;1~30f/s variable
Image output	Main stream: 1280*720, sub-stream: 704*576;
Network interface	1 RJ45, 10/100M Ethernet adaptive interface; support RTSP / FTP / PPPOE / DHCP / DDNS / NTP / UPnP network protocols;
Network connection	Supports Wireline、Wi-Fi, a key WPS function;
Hardware features	Support a key reset function
Audio interface	1ch input, electrical level 2Vp-p, impedance $1k\Omega$, support pickup input; 1ch output,
	impedance 16Ω , $30mv$ output power, support to connect the headset or power amplifier
Audio processing	G.711 standard compression, support two-way Bidrectional Talk, support for audio and video synchronization
Alarm input	1 channel
Alarm output	1 channel
Micro SD card	Support,maximum 32G
Other function	Support WEB configure, support for OSD, support real-time video transmission, support mobile surveillance, support for mobile detection alarm center after the screen pop-up reminders and linkage; supports JPEG capture; support unified client remote monitoring software, MYEYE platform system applications; provide perfect the SDK development package;
ONVIF	Unsupport
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC5V
Other	Restore factory settings button interface, support photo resistor linkage;
Explain	Does not accept any custom.

http://www.xiongmaitech.com

Head office:BuildingNo.9,Yinhu innovation park,Hangzhou City