

IPM-53H13PE-WRC
Features:

- Supports Wi-Fi, a key WPS function;
- Support Micro SD card, up to 32G;
- Support 3D DNR, DWDR;
- Support for mobile video surveillance (iOS, android);
- Support Web, CMS, platform management software MYEYE, Provide SDK ;
- Support cloud service, network penetration, alarm information pushed to phone ,etc.


Parameters:

Model	IPM-53H13PE-WRC
System structure	Embedded RTOS, dual-core 32-bit DSP (Hi3518E), pure hard compression, watch dog
sensor	Match and use with ISM-5313PS-R, color 0.01Lux@F1.2, black/white 0.001Lux@F1.2
Video compression	H.264, support dual stream, AVI; 0.1M~6Mbps variable; 1~20f/s variable
Image output	Main stream: 1280*960(18fps), 1280*720, sub-stream: 704*576;
Network connection	Supports Wi-Fi, a key WPS function;
Hardware features	Support a key reset function
Audio interface	1ch input, electrical level 2Vp-p, impedance 1kΩ, support pickup input; 1ch output, impedance 16Ω, 30mv output power, support to connect the headset or power amplifier
Audio processing	G.711 standard compression, support two-way Bidirectional Talk, support for audio and video synchronization
Alarm input	1 channel (Self welding Phoenix terminal)
Alarm output	1 channel (Self welding Phoenix terminal)
Motor interface	A horizontal motor interface, a vertical electrical interfaces, a limit switch;
Micro SD card	Support, maximum 32G
Lightning Protection	Power lightning protection, in line with national standards GB/T17626.5, the international standard IEC61000-4-5.
Other function	Support WEB configure, support for OSD, support real-time video transmission, support mobile surveillance, support for mobile detection alarm center after the screen pop-up reminders and linkage; supports JPEG capture; support unified client remote monitoring software, MYEYE platform system applications; provide perfect the SDK development package;
ONVIF	Unsupport
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC5V
Other	Restore factory settings button interface, support photo resistor linkage;
Explain	Does not accept any custom.