

**SD-FA6110H-X30R
AHD IR SPEED DOME CAMERA**



Product Features:

- 1、Adopt high performance sensor, image clear, soft.
- 2、Support IR-CUT, Day-night surveillance, realize Day & Night surveillance, No color cast, distortionless.
- 3、AHD-M@AHD video output.
- 4、Transmission distance reach to 500m.
- 5、Need to connect to back-end AHD DVR;
- 6、Support ultralow illumination.
- 7、Auto electronic shutter, applied in different surveillance environment.

Application:

Applied in different surveillance location such as corridor, large gymnasium, meeting room, waiting room, etc.

Order Item:

SD-FA6110H-X30R

Shell Size:

Specifications:

Model	SD-FA6110H-X30R
Camera	
Image sensor	1/3" APTINA CMOS
Signal System	AHD-M@AHD
System standard	PAL/NTSC
Image pixel	1280*720
Minimum Illumination	Color 0.01Lux @(F1.2,AGC ON),0 LUX with IR B/W 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR
WDR	Digital WDR
DNR	2D/3D
Electronics Shutter	1/1 - 1/10,000s
Day&Night	Support IR-CUT
Lens	
Focal length	4.3 to129mm (F1.6-F5.0)
Optical Zoom	30x
Function	
IR LEDS Distance	120m
P/T Range	Level: 0°~360°continuous rotation, Vertical: -15°~90° automatic turning180°continuous monitoring
Preset point	255
Auto Mode	Support 4 lines auto cruiser, 4 auto patrol tracks, 4 auto scan.
Video in/out	
Analog interface	1.0Vpp / 75Ω, NTSC/ PAL, BNC
RS485 Control	Half-duplex mode, support PTZ control and online upgrade, protocol support: Chinese security industry protocols, Pelco P / D, protocol support automatic recognition
General	
Power supply	DC 12V±10% / 4A; power consumption≤35W
Working environment	Temperature-30~65℃; Humidity<90%
protection range	IP66
Dimension	Φ226mm*362.8mm
Weight	About 5.0Kg