

SD-MN4113U-X10R
1.3 Megapixels CMOS IR Dome camera



Features

- HD 960P resolution; image clarity and detail;
- Support IR-CUT, to achieve day and night surveillance;
- support three-dimensional intelligent positioning function, enable tracking and enlarge by clicking;
- Advanced video compression technology, ultra-low bit-rate, high-definition picture quality;
- Support several kinds of phone remote monitoring (iOS, Windows Mobile, BlackBerry, Symbian, Android);
- Supports multiple browser access (IE、Chrome、Firefox、Safari);
- Automatic electronic shutter function, adapt to Scenarios different environmental monitoring;
- Support ONVIF standard;
- Supporting web, CMS, center platform management software MYEYE, provide SDK development;

For occasions:

Need to be applied to a wide range of monitoring indoor places such as corridors aisle, large venues, conference rooms, waiting rooms and other indoor places.


Model:

SD-MN4113U-X10R

Dimensions:

Parameters

Model	SD-MN4113U-X10R
Camera	
Image Sensor	1/3" APTINA CMOS
Video Format	PAL/NTSC
Image Resolution	Main stream:1280*960,1280*720;Sub-stream (D1)
Lowest Illumination	Color 0.01Lux @(F1.2,AGC ON),0 LUX with IR B&W 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR
Wde Dynamic	Digital Wide Dynamic
Digital Noise Reduction	2D/3D Noise Reduction
Electronic Shutter	1/1 - 1/10,000s
Day and Night Mode	Support IR-CUT
Shot	
Focal length	4.63 to 46.3mm (F2.0)
Optical magnification	10 times
Function	
Infrared Distance	50m
Rotation range	Horizontal: 0 ~ 360 °continuous rotation; Vertical: -2 °~ 90 °continuous monitoring after auto flip 180 °
Preset point	50
Automatic mode	Supports 8 auto cruise
PTZ function	Support the free movement, support three-dimensional positioning, support humane focal length / Speed automatic matching, support power memory function
Network protocol	TCP/IP, HTTP, DDNS, DHCP, NTP, PPPoE, FTP,SMTp,RTSP,RTP
Storage function	Network storage, support for microSD card storage
Input / Output	
Network Interface	1 RJ45 interface, 10M/100M adaptive Ethernet interface,
Power	DC 12V
General Specifications	
Work Environment	Temperature -10 ~ 60 °C; Humidity <90%
Protection class	4000Vlightningprotection,surgeandanti-surgeprotection,meets GB/T17626.5 four standard
Size	Φ142mm*135mm
Weight	About 940g



梦

