

CMOS Indoor Box IP Camera Series



Model:

IPC-AT5110PL , IPC-AT5313PL, IPC-AT5320PL ,IPC-AT5120PL

Feature:

- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, super high-definition picture quality.
- Support various information superimposed (ID、IP、DDNS and so on), convenient to operate.
- Support two-way audio and dual-stream
- Plug and Play,multipleNetworkCloud security and surveillance
- support various mobile long-distance monitoring (iPhone,Windows Mobile, BlackBerry,Symbian, Android)
- Support multiple web browsers (IE、Chrome、Firefox、Safari)
- support WIFI/3G(USB extend)
- support auto electronic shutter, adapt to different monitoring environment.
- complete functions:PTZ control, alarm,a master reset
- web and CMS supporting、 central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF.

Specification

model	IPC-AT5110PL	IPC-AT5313PL	IPC-AT5320PL	IPC-AT5120PL
camera				
image sensor	1/4" OV 9712 CMOS	1/3" AR0130ultra-low illumination CMOS	1/2.8" SONY IMX222ultra-low illumination CMOS	1/2.7" OV2710 CMOS
Video standard	PAL/NTSC			
min.illumination	Color:0.6Lux @ (F1.2,AGC ON) black/white:0.08 Lux @ (F1.2,AGCON)	Color 0.01Lux @ (F1.2,AGC ON) black/white: 0.001 Lux @ (F1.2,AGCON)		Color 0.6Lux @ (F1.2,AGC ON) Black/white 0.08 Lux @ (F1.2,AGC ON)
shutter	1/50(1/60)s - 1/10,000 s			
lens	no			
day/night	IR-CUT			
lens mount	C/CS interface			
automatic diaphragm	DC			
compression				
video compression	H.264 HighProfile, JPEG snapshot			
bite rate	32 Kbps~6Mbps		32 Kbps~8Mbps	
audio compression	G.711a			
image				
frame rate	50Hz: 25fps(1280*720) 60Hz: 30fps(1280*720)	50Hz: 25fps(1280*720) 25fps(1280*960) 60Hz: 30fps(1280*720) 25fps(1280*960)	50Hz:25fps(1920*1080) 60Hz:30fps(1920*1080)	
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client.			
network				
storage	Local SD storage ,Network storage			
intelligent alarm	Motion detection, video loss, cable break, IP address conflicts			
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP(HTTPS,SIP ,802.1x,IPv6)			
basic	one key reset, anti-flicker, dual-stream, heartbeat, password protection			
interface				
Audio input	1ch 3.5mm JACK			
Audio output	1ch 3.5mm JACK			
net interface	One RJ45 10M/100M,one RS-485 interface			
alarm input	2ch switching value			
alarm output	1ch switching value			
USB	1ch,WIFI/3G			
general				
Operating condition	-10℃~60℃,humidity less than 90%(non-condensing)			
power supply	DC12V±10%			
dimension	144mm*78.5mm*56.5mm			